

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Application No. :

U.S. National Serial No. :

Filed :

PCT International Application No. : PCT/DE2004/001375

VERIFICATION OF A TRANSLATION

I, Susan ANTHONY BA, ACIS,

Director of RWS Group Ltd, of Europa House, Marsham Way, Gerrards Cross, Buckinghamshire, England declare:

That the translator responsible for the attached translation is knowledgeable in the German language in which the below identified international application was filed, and that, to the best of RWS Group Ltd knowledge and belief, the English translation of the amended sheets of the international application No. PCT/DE2004/001375 is a true and complete translation of the amended sheets of the above identified international application as filed.

I hereby declare that all the statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the patent application issued thereon.

Date: December 15, 2005

Signature :



For and on behalf of RWS Group Ltd

Post Office Address :

Europa House, Marsham Way,
Gerrards Cross, Buckinghamshire,
England.

PCT/DE2004/001375

- 16 -

New claims 1 and 8

1. A method for patterning an unpatterned organic
5 layer (3; 13), in particular of organic circuits,
characterized by

- pressing patterning means (2; 12) at a
predetermined, elevated temperature and at a
predetermined pressure into the organic layer (3;
10 13), the patterning means making contact with the
organic layer (3; 13) but not piercing it, and the
organic layer (3; 13) being permanently patterned
and pierced after the pressing-on.

15 8. A device for patterning organic layers, in
particular of organic circuits, characterized by
patterning means (2; 12) having predetermined
dimensions, the patterning means, at a predetermined,
elevated temperature and at a predetermined pressure,
20 after making contact with the organic layer (3; 13),
patterning the latter permanently because the organic
layer (3; 13), after contact has been made, retreats at
the contact points in such a way that depressions
and/or holes arise there.